



Barrikade®

System data sheet

Barrikade Mono Deco *Selflevelling decorative UV resistant polyurethane system*

S.01 - 01.15

Description:

Barrikade Mono Deco is a seamless decorative flooring system based on solvent-free, UV-resistant polyurethane and special fillers.

Barrikade Mono Deco is mainly suitable for use on new or old concrete. The system provides a very attractive surface.

Applications:

Barrikade Mono Deco gives a smooth, waterproof and hard surface and is suitable in areas where hygiene, cleaning friendliness and durability is important, and where a decorative expression is required.

Properties:

Chemical:

Barricade Mono Deco provides a seamless and waterproof surface with good chemical resistance to alkalis, oil, fat and salt but limited resistance to acids with high concentration.

Mechanical:

Barricade Mono Deco has very good abrasion resistance.

Flexibility

Barricade Mono Deco has a good flexibility, making it able to absorb movements in the substrate and to absorb impact without cracking. It is also comfortable to walk on-

Pretreatment of concrete:

Finish: Grinding or blasting

The surface should be in accordance with tolerance class 2 or better.

Primer: Barrikade PB

Binder Barrikade Mono Deco mixed with special filler A:B:C = 1:0,94:2,13

Colours:

See color chart

Installation:

Install **Barrikade Mono Deco** as a traditional self-leveling epoxy system with distance tear or trowel. Finish with spike rolling.

Material consumption:

Barrikade Mono Deco is supplied as a three-component system. Material consumption for binder mixed with filler is 3- 3.5 kg / m².

