

System Data Sheet

Monoart



System description:

Monoart is a seamless decorative flooring system. The system consists of a primer, a single coloured undercoat and a topcoat with special colour effects. Eventually a cementitious, flexible undercoat can be used to increase comfort and reduce sound.

The system has a thickness of 1,5-4 mm depending on the undercoat.

Monoart is delivered in 10 standard colours. This standard colour is achieved by using a black undercoat. The colour aspect can be changed by using other colours in the underlayer. It is also possible to mix two or more colours to achieve special effects, or to provide patterns, logos or pictures in the undercoat, that will be visible through the topcoat.

User areas:

Monoart is designed for all kind of public or domestic areas where a seamless, hard wearing and decorative floor finish is required.

- Shopping malls
- Shops
- Receptions
- Entrances
- Offices
- Private houses
- etc

Monoart is well suited for renovation of existing floors due to its low thickness and good adhesion.

Monoart is a seamless system. Joints are only needed where there is an expansion joint in the substrate.

Properties: Monoart provides a waterproof, hard wearing, UV resistant, scratch resistant and beautiful surface that is easy to clean.

Monoart has excellent mechanical properties.

System:

Epoxy primer:

Barrikade EP-PB

Undercoat:

**Monoart base coat or
Barrikade Stoneflex**

Topcoat:

Monoart 0,75-1,0 kg/m²

Protection

Use Barrikade metallic polish, gloss or mat.

The gloss polish is applied in two layers and high speeded after two days to increase gloss. The mat version is also applied in two layers, and is ready to use without further treatment.

Both polishes are walkable after a few hours. Full curing in 48 hours.



StoCretec Flooring AS,
Værftsgt. 7 A, N-1510 Moss,
Tel. 69 27 30 00 - Fax. 69 27 46 30
E-post: stocretec.no@sto.com
www.stocretec.no